

KILN FURNITURE

KILN SHELVES			
CODE	SIZE		\$
KS1	305 x 305 x 8mm	(12" x 12" x 5/16")	34.80
KS2	305 x 305 x 12mm	(12" x 12" x 1/2")	47.50
KS3	330 x 330 x 13mm	(13" x 13" x 1/2")	54.80
KS4	340 x 340 x 15mm	(13 3/8" x 13 3/8" x 5/8")	71.10
KS5	400 x 400 x 10mm	(15 3/4" x 15 3/4" x 1/2")	82.10
KS6	400 x 400 x 15mm	(15 3/4" x 15 3/4" x 5/8")	99.70
KS7	400 x 400 x 20mm	(15 3/4" x 15 3/4" x 3/4")	110.70
KS8	400 x 400 x 25mm	(15 3/4" x 15 3/4" x 1")	133.15
453320	457 x 330 x 20mm	(17 3/4" x 13" x 3/4")	104.00
454512	450 x 450 x 12mm	(17 3/4" x 17 3/4" x 1/2")	104.75
454515	450 x 450 x 15mm	(17 3/4" x 17 3/4" x 5/8")	127.20
KS11	450 x 450 x 20mm	(17 3/4" x 17 3/4" x 3/4")	141.40
KS12	450 x 450 x 25mm	(17 3/4" x 17 3/4" x 1")	169.80
505012	500 x 500 x 12mm	(19 5/8" x 19 5/8" x 1/2")	127.35
505015	500 x 500 x 15mm	(19 5/8" x 19 5/8" x 5/8")	155.05
535320	530 x 530 x 20mm	(21" x 21" x 3/4")	196.15
555520	550 x 550 x 20mm	(22" x 22" x 3/4")	216.50
KS14B	610 x 305 x 15mm	(24" x 12" x 5/8")	119.45
KS15	610 x 305 x 20mm	(24" x 12" x 3/4")	134.40
KS15B	610 x 305 x 25mm	(24" x 12" x 1")	160.80
KS17	610 x 610 x 20mm	(24" x 24" x 3/4")	256.70
KS17B	610 x 610 x 25mm	(24" x 24" x 1")	299.00
614515	610 x 457 x 15mm	(24" x 18" x 5/8")	170.90
KS19	610 x 457 x 20mm	(24" x 18" x 7/8")	212.75
KS19B	610 x 457 x 25mm	(24" x 18" x 1")	234.30
Cutting Fee per cut			5.00

PROPS (45mm Diameter)		
CODE	SIZE	\$ ea
P1	25mm (1")	1.95
P2	50mm (2")	3.90
P3	75mm (3")	5.85
P4	100mm (4")	7.80
P5	125mm (5")	9.75
P6	150mm (6")	11.70
P7	175mm (7")	13.65
P8	200mm (8")	15.60
P9	225mm (9")	17.55
P10	250mm (10")	19.50
P11	275mm (11")	21.45
P12	300mm (12")	23.40
P13	325mm (13")	25.35
P14	350mm (14")	27.30

STILTS—STEEL POINTED, 3 POINT STAR
Suitable for firing to 1160°C only -
above this the wire will bend

CODE	SIZE (Point to Point)	\$
SS2	25mm	4.75
SS3	30mm	5.10
SS35	35mm	5.90
SS55	55mm	6.95
SS70	70mm	7.50
SS85	85mm	8.10
SS120	125mm	12.00

SPST **SPEEDY STILTS (18 Pack) Suitable to 1160°C** 17.65



SS	STILT STONE	6.50



SPURS - DOUBLE POINTED, 3 POINT STAR
Suitable for firing to 1100°C only

CODE	SIZE (Point to Point)	\$
SSC50	50mm	0.75
SSC55	55mm	0.80